

# STYLE SA PRODUCT NUMBERS

Below Is An Example Of Building A Part Number For Ordering A Strainer

Size	Pressure Class	End Conn.	Strainer Type		Body Material	Perf or Mesh	Screen Type	Screen Material		Gasket Type	Cover Conn.	Origin		Style
6	5	RF	Y	-	CS	062	P	34	-	G	B	B	-	SA

Description: 6" Class 600 RF Flange Y-Strainer, Carbon Steel Body, 1/16" Perforated 304ss, Spiral Wound 304ss Gasket - Graphite filled, Bolted Cover, Domestic, Style SA.

**Size**

--

**Pressure Class**

Ordering Number	ASME Pressure Class
5	600
6	900
7	1500
8	2500

**End Connection**

Ordering Number	End Connection
RF	Raised Face Flange
B8	Butt Weld, Sch 80/80s

**Strainer Type**

Ordering Number	Strainer Type
Y	Y-Pattern Strainer

**Body Material**

Ordering Number	Body Material
CS	Carbon Steel (ASTMA 216, WCB)
FS	Forged Steel (ASTMA 105)

**Perf. or Mesh**

Ordering Number	Perf. or Mesh
033	1/32"
045	3/64"
062	1/16"
094	3/32"
125	1/8"
156	5/32"
188	3/16"
250	1/4"
375	3/8"
500	1/2"
750	3/4"
M20	20 Mesh
M30	30 Mesh
M40	40 Mesh
M50	50 Mesh
M60	60 Mesh
M80	80 Mesh
M100	100 Mesh
M150	150 Mesh
M200	200 Mesh
M300	300 Mesh
X	Special

**Screen Type**

Ordering Number	Screen Type
P	Perforated
M	Mesh
L*	Perforated with Mesh Lining
S	Perforated with Mesh Lined Start Up
X	Special

\*20 mesh and finer screens must be reinforced with perforated screen.

**Screen Material**

Ordering Number	Screen Material
34	Type 304 Stainless Steel
36	Type 316 Stainless Steel
BR	Brass
ML	Monel
TI	Titanium
HC	Hastelloy C276
DS	Duplex Stainless Steel
X	Special

**Gasket Type**

Ordering Number	Gasket Type
G	Spiral Wound SS (304) - Graphite Filler
T	Spiral Wound SS (316) - Teflon Filler
S	Spiral Wound SS (316) - Graphite Filler
M	Spiral Wound Monel - Graphite Filler
X	Special

**Cover Connection**

Ordering Number	Cover Connection
B	Bolted

**Origin**

Country Code	Origin
B*	Domestic
I	Import

\*Assembled, painted, and tested in the U.S. w/ foreign castings and Domestic components.