

HOW TO ORDER

STYLE SSA7() PRODUCT NUMBERS

Below Is An Example Of Building A Part Number For Ordering A Strainer

Size	Pressure Class	End Conn.	Strainer Type		Body Material	Perf or Mesh	Screen Type	Screen Material		Gasket Type	Cover Conn.	Origin		Style
4	4	RF	Y	-	HC	125	P	34	-	M	B	I	-	SSA7HC

Description: 4" Class 300 RF Flange Y-Strainer, Hastelloy C276 Body, 1/8" Perforated 304ss, Spiral Wound Monel Gasket - Graphite filled, Bolted Cover, Import, Style SSA7HC.

Size	Pressure Class	End Connection	Strainer Type																		
<input type="text"/>	<table border="1"> <thead> <tr> <th>Ordering Number</th> <th>ASME Pressure Class</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>150</td> </tr> <tr> <td>4</td> <td>300</td> </tr> </tbody> </table>	Ordering Number	ASME Pressure Class	2	150	4	300	<table border="1"> <thead> <tr> <th>Ordering Number</th> <th>End Connection</th> </tr> </thead> <tbody> <tr> <td>RF</td> <td>Raised Face Flange</td> </tr> <tr> <td>B4</td> <td>Butt Weld, Sch 40/40s</td> </tr> <tr> <td>B8*</td> <td>Butt Weld, Sch 80/8s</td> </tr> </tbody> </table> <p><small>*Available in Class 300 only. Consult Factory prior to ordering.</small></p>	Ordering Number	End Connection	RF	Raised Face Flange	B4	Butt Weld, Sch 40/40s	B8*	Butt Weld, Sch 80/8s	<table border="1"> <thead> <tr> <th>Ordering Number</th> <th>Strainer Type</th> </tr> </thead> <tbody> <tr> <td>Y</td> <td>Y-Pattern Strainer</td> </tr> </tbody> </table>	Ordering Number	Strainer Type	Y	Y-Pattern Strainer
Ordering Number	ASME Pressure Class																				
2	150																				
4	300																				
Ordering Number	End Connection																				
RF	Raised Face Flange																				
B4	Butt Weld, Sch 40/40s																				
B8*	Butt Weld, Sch 80/8s																				
Ordering Number	Strainer Type																				
Y	Y-Pattern Strainer																				

Body Material	
Ordering Number	Body Material
A2	Alloy 20 (ASTMA 351, Grade CN7M)
HC	Hastelloy C276 (ASTMA 494, Grade CW12MW)
ML	Monel (ASTMA 494, Grade M35-2)
T7	Titanium (ASTM B 367, Grade PD7B)
DP	Duplex (ASTMA 351, Grade CD4MCu)

Perf. or Mesh	
Ordering Number	Perf. or Mesh
033	1/32"
045	3/64"
062	1/16"
094	3/32"
125	1/8"
156	5/32"
188	3/16"
250	1/4"
375	3/8"
500	1/2"
750	3/4"
M20	20 Mesh
M30	30 Mesh
M40	40 Mesh
M50	50 Mesh
M60	60 Mesh
M80	80 Mesh
M100	100 Mesh
M150	150 Mesh
M200	200 Mesh
M300	300 Mesh
X	Special

Screen Type	
Ordering Number	Screen Type
P	Perforated
M	Mesh
L*	Perforated with Mesh Lining
S	Perforated with Mesh Lined Start Up
X	Special

*20 mesh and finer screens must be reinforced with perforated screen.

Screen Material	
Ordering Number	Screen Material
34	Type 304 Stainless Steel
36	Type 316 Stainless Steel
BR	Brass
ML	Monel
TI	Titanium
HC	Hastelloy C276
DS	Duplex Stainless Steel
X	Special

Gasket Type	
Ordering Number	Gasket Type
G	Spiral Wound SS (304) - Graphite Filler
T	Spiral Wound SS (316) - Teflon Filler
S	Spiral Wound SS (316) - Graphite Filler
M	Spiral Wound Monel - Graphite Filler
X	Special

Cover Connection	
Ordering Number	Cover Connection
B	Bolted

Origin	
Country Code	Origin
B*	Domestic
I	Import

*Assembled, painted, and tested in the U.S. w/ foreign castings and Domestic components.