

BODY PRESSURE & TEMPERATURE RATINGS - NON SHOCK			
NOM. RATING	MEDIA	1/2" to 8"	
900# SCH 160	STEAM	710 PSI @ 1150°F	
(BUTT WELD)	W.O.G.	2160 PSI @ 100°F	

	PARTS LIST			
ITEM DESCRIPTION MATERIAL		MATERIAL		
1	BODY	STAINLESS STEEL (ASTM A 351, GRADE CF8M)		
2	SCREEN	STAINLESS STEEL (304)		
3	3 GASKET SPIRAL WOUND STAINLESS STEEL (304) – WITH GRAPHITE FILL 4 COVER STAINLESS STEEL (ASTM A 351, GRADE CF8M)			
4				
5	STUDS	ALLOY STEEL (ASTM A 193, GRADE B)		
6	HEAVY HEX NUTS	ALLOY STEEL (ASTM A 194, )		

	SIZE	DIMENSIONS (in)		WEIGHT (lbs)	
Product Number†	SILL	А	В	WEIGHT (IDS)	
1/26B9Y-36033P34-GB	1/2	7-3/8	4-1/4	20	
3/46B9Y-36033P34-GB	3/4	8-3/16	4-3/4	30	
16B9Y-36033P34-GB	1	9-1/16	5-3/4	52	
11/46B9Y-36033P34-GB	1-1/4	12	6-3/4	65	
11/26B9Y-36033P34-GB	1-1/2	12	6-3/4	65	
26B9Y-36033P34-GB	2	13-15/16	7-1/2	93	
21/26B9Y-36033P34-GB	2-1/2	17-1/2	10-3/4	185	
36B9Y-36033P34-GB	3	17-1/2	10-3/4	185	
46B9Y-36033P34-GB	4	23-3/8	15	250	
66B9Y-36045P34-GB	6	31	18-7/8	560	
86B9Y-36045P34-GB	8	Consult Factory	Consult Factory	Consult Factory	

<sup>†</sup>See "Style SSA Product Number Configuration" for additional options.

<b>◄</b> ————————————————————————————————————	-
B	
2	
3 56	

## STANDARD SCREENS SUPPLIED

SIZE SCREEN PERFO				RFORATION	
SIZE	SCREEN	FOR STEAM OPEN		FOR LIQUID	OPEN
in	GAGE	in	AREA	in	AREA
1/2 to 4	28	1/32	29%	1/16	30%
5 to 8	24	3/64	33%	1/8	43%

Standard screens supplied are for **steam service**, unless otherwise specified. Options: Other perforations, meshes, and screen materials are available.

		DRAWING NO.
K KECK	AL 90820	
3400 CLEVELAND SKO	OKIE ILLINOIS	
DIMENSIONAL ASSI	PART NO. 6B9Y-36	
1/2" to 8" 900# Butt Weld	SCALE: NTS	
	DATE: 09/22/2014	
MAT'L: (As Noted Above)	REQ	DR. BY DSF