

HOW TO ORDER BVSC BALL VALVES

Below Is An Example Of Building A Part Number For Ordering A Ball Valve

Valve Style	End Connection	Port Size	Body/Trim Material	Seat Material	Seal Material	Handle	Size
BVSC	TH	F	SS	R	G	SL	150

Description: ASME Class 900 Seal Welded Ball valve with threaded end connections, full port, CF8M body and 316SS trim, Reinforced PTFE seats, Graphite seal, with 304SS Latch Lock Lever in 1-1/2" size.

Product #: BVSCTHFSSRGSL-150

VALVE STYLE

Ordering Number	Valve Style
BVSC	ASME Class 900 Seal Weld

END CONNECTION

Ordering Number	End Connection
TH	NPT
SW	Socket Weld
MF	MNPT x FNPT
WT	Socket Weld x FNPT

PORT SIZE

Ordering Number	Port Size
F	Full

BODY/TRIM MATERIAL

Ordering Number	Body/Trim
CS	Carbon Steel w/ 316SS Trim
SS	CF8M w/ 316SS Trim

SEAT MATERIAL

Ordering Number	Seat Material
R	Reinforced PTFE
P	PEEK

SEAL MATERIAL

Ordering Number	Seal Material
G	Graphite

HANDLE

Ordering Number	Handle
SL	304SS Latch Lock
SO*	304SS Oval
LO*	304SS Locking Oval

*1/2", 3/4", and 1" sizes only.

SIZE

Ordering Number	Size	Ordering Number	Size
025	1/4"	100	1"
038	3/8"	125	1-1/4"
050	1/2"	150	1-1/2"
075	3/4"	200	2"